

customize your dream

Al Camera One-Stop Solution

Model	: W431	Product Features
		♦ Easy to install and use
		♦ Clear and smooth video browsing: intelligent transmission giving full play to capabilities of the network
		Online firmware upgrade, and synchronous updating of the functions and experience
		◆ Two-way voice intercom supported; echo eliminated; noise suppressed
		◆ Compatible with Android; remote real-time monitoring supported with the IOS intelligent terminal
		◆ 4-megapixel startight high resolution (2560X1440) for clear picture quality
		◆ Dual-source lighting for night vision (night vision distance = 7 m) comprising infrared lamp / white-light
		source: color images available for night vision. The built-in rechargeable lithium battery with long battery life functions for up to 6 months under normal
		circumstances and can stand by for 12 months
		◆ 2.4G Wi-Fi supported (IEEE802.11b/g/n)
		◆ Cloud storage, Micro SD card (up to 128GB) and mobile phone video recording supported
		QR code intelligent connection and network allocation supported
		 Supporting human contour detection, activity zone, vechicle detection, pet snapshot and package inspection (value added service required)
		◆ IP65 Easy installation: support 1/4 universal screw bracket and magnetic suction bracket
W431	Items	Specifications
Master Processor	SOC Sensor	ARM 1/3" color CMOS Sensor
Image Sensor	Lens Visual angle	M12, f: 2.97mm, F1.6, 4-megapixel H (horizontal) 105 degrees; V (vertical) 58.3 degrees; D (diagonal) 123.6 degrees
	Minimum Illumination	0.01 Lux
Audio	Input/Output	Two-way voice intercom available (built-in Microphone and speaker)
	Audio Compressing Method Video Compressing Method	AAC H.265
	Lighting Frequency	50Hz, 60Hz
Video	Image Frame Rate	15 fps
		2560*1440P
	Light Source for Night Vision	Mid-power infrared lamp (850nm in wavelength) / dual-source white-light source with an irradiation distance of 7m
Network	Wireless Network	2.4G Wi-Fi (IEEE802.11b/g/n), built-in antenna
	Protocols Supported IP Address Supported	TCP/IP, UDP/IP, DHCP, RTMP, MUTP Dynamic IP address supported
Al	Intelligent Features	Human contour detection, activity zone, vechicle detection, pet snapshot and package inspection
Alarm Notification	Alarm Methods	Alarm push by mobile APP, white light flashing and alarm sound
Wake-up	Wake-up Method	PIR body induction wake-up, and remote wake-up
Video Recording	Recording Method	Alarm triggered recording, and manual recording
	Video Storage	Cloud storage, local Micro SD card, and mobile phone memory
Indicator Lamps	LED Indicator	RGB tri-color lamp indicating the status of power/network signal/functionality
	Capacity Removability	5200mAh/6700mAh(Optional) Unremovable
	Battery Life	6 months (provided that 20 10s videos are recorded per day)
Battery	Standby Time	1 year
	Charging Voltage	DV 5V+-5%/1.5A
	Charge Time	Within 10 hours
	Protection Method	IP65 is dustproof and waterproof; over-current/over-discharge/over-charge/short circuit/charging protection at high & low temperatures
Power Consumption	Standby Power Consumption	1.93mW(4V 0.48mA)
	Power Consumption of	1.11W(3.87V 288mA)
	Daytime Operation	THE THOUSE AND THE STATE OF THE
	Power Consumption of Operation at Night	2.02W(3.73V 542mA)
	Power Supply	1 Micro USB interface
Interfaces	SD Card	1 Micro SD card (up to 128GB supported)
	Keys	1 reboot key and 1 on/off key
Installation Method	Installation Method	Magnet and 1/4 universal screw holes
Environment	Dustproof and waterproof	IP65
	Operating Environment Storage Environment	-10° ~ 45°C /10% ~ 80% (no condensation) -20°C ~ 60° /0% ~ 90% (no condensation)
	Size (LxWxH)	84mm*62mm*96mm(without bracket)
Specifications		ABS+PC
Specifications	Material + Process	ADSTIC
Specifications Certifications	Color Certificate	White with high gloss CE, FCC, RoHS, WEEE, MSDS, UN38.3, UL62368